



Engine Rebuilding Equipment, Inc.

Rogers Machine Company
5775 Bridgeview Center
Saginaw, Mi 48604

USA & Canada
Phone
Fax
Web Site

(800) 248-5062
(989) 754-3611
(989) 754-1696
www.rmcequipment.com



Hydraulic Crankshaft Grinders



RMC-1200 shown


RMC Crankshaft Grinders are designed with state-of-the-art technology to utilize the quickest, most efficient crankshaft setup system available. RMC's built-in features benefit the serious rebuilder who is grinding welded crankshafts or crankshafts with unknown stroke. High performance rebuilder's particularly appreciate the ability to modify or maintain the existing stroke with the utmost accuracy and repeatability.

Dedicated to serving your engine rebuilding equipment needs.

RMC Crankshaft Grinders are ... Fast ... Accurate ... Dependable

RMC Crank Grinders use work heads with 4-way cross slides with an advanced locking system permitting quick centering of the crankshaft. Heavy duty cast iron construction assures a lifetime of superior accuracy and dependability. Whatever your crank grinding needs, **RMC** has a model to do the job your customers demand - at a price you can afford.

Specifications	RMC-1200	RMC-1500
Distance between centers	52.00"	61.00"
Distance between chucks	50.00"	60.00"
Height of centers over table	8.60"	9.80"
Swing over table	17.30"	19.70"
Max offset of centers	3.10"	4.00"
Max grinding diameter	7.10"	8.10"
Fast hyd wheelhead traverse	3.10"	4.50"
Hand wheelhead feed distance	5.90"	6.50"
Hand wheelhead feed grads	0.0002"	0.0002"
Wheelhead feed per revolution	0.04"	0.04"
Table traverse handwheel revs	0.44"	0.50"
Fast hydraulic table traverse	118"/min.	118"/min.
Grinding wheel speeds	1000-1150 rpm	900-1000 rpm
Max grinding wheel diameter	24.00"	28.00"
Max width of grinding wheel	2.50"	2.75"
Diameter of chucks	7.10"	7.10"
Chuck hold diameter	8.60"	8.60"
Steady rest capacity	1-3.00"	1-3.94"
Workhead spindle speeds	35-70 rpm	20-30-40-60rpm
Max weight on centers	440 lbs	440 lbs
Max weight on rests	660 lbs	1,100 lbs
Wheelhead motor	5 hp	7 hp
Wheelhead spindle motor	1/2 - 3/4 hp	3/4 - 1 hp
Hydraulic power motor	1 hp	1 hp
Cooling pump	1/12 hp	1/12 hp
Length x Height x Width	129x53x61"	157x59x66"
Work space required	181 x 59"	219 x 55"
Net/Shipping weight	6173 / 7055 lbs	7275 / 8378 lbs




Standard Equipment

Grinding wheel & hub, narrow steady rest w/dial indicator, universal steady rest (1500), device for setting length of stroke, throw setting device, set up device w/dial indicator, dresser w/diamond, wheel balancing arbor, pair extra counterweights, grinding motor reduction pulley, pair coolant nozzles and set of wrenches, service tools and operator's manual.



Control panel is operator friendly and conveniently located for fast easy access throughout the grinding operation.



Self contained cooling system insures proper coolant flow over the work piece to help prevent wheel loading and poor grinding results.



Massive Head and Tail Stocks feature face plate system with positive stop and trim adjustment to make short work of setup time. Shown below with steady rest.



In order to bring you the most advanced features as soon as possible, all features, descriptions and technical specifications are subject to change.

Engine Rebuilding Equipment, Inc.

5775 Bridgeview Center

Saginaw, Mi 48604

Web site: www.rmcengine.com

USA & Canada

Phone

Fax

(800) 248-5062

(989) 754-3611

(989) 754-1696